

KOYU

GASOLINE GENERATOR SET WITH AVR



KY 1200



KY 2500



KY 3000



KY 3000E



KY 5000E



KY 6500W-SE / KY 8000W-SE

DIJAMIN 100% TEMBAGA

SPECIFICATIONS KOYU GASOLINE GENERATOR SET

Ctg. No. 1 71 11 01

Model		KY1200	KY2500	KY3000	KY3000E	KY5000E	KY6500W-SE	KY8000W-SE
GENERATOR	Type	Brush less single phase						
	Voltage reg.	AVR						
	Frequency (HZ)	50						
	Rated AC voltage (V)	220 V						
	Rated AC output (KVA)	1.0	2.0	2.5		4.0	5.0	5.5
	Max. AC output (KVA)	1.1	2.2	2.8		4.5	5.5	6.0
	Power factor	1.0						
Model		CGE 154	CGE 160	CGE 200	CGE 200	CGE 340	CGE 390	CGE 420
ENGINE	Type	4 - stroke, OHV, Forced air cooled						
	Bore x stroke (mm)	54 x 38	68 x 45	68 x 54		82 x 64	88 x 64	90 x 66
	Displacement (mm)	86.5	163	196		337	389	420
	Max. output (HP/rpm)	2.4 / 3600	5.5 / 3600	6.5 / 3600		11 / 3600	13 / 3600	15 / 3600
	Fuel	Unleaded gasoline						
	Fuel tank capacity (L)	5	15			25		
	Continuous operating hours (h)	15	13	11		10	9	8
	Oil capacity (L)	0.4	0.6			1.1		
	Starting system	Recoil			Recoil / Electric starter			
	Ignition system	T.C.I						
	Operating noise level(db)	68	67			72	60	
	STANDARD FEATURES	Fuel gauge	✓	✓	✓	✓	✓	✓
Voltmeter		✓	✓	✓	✓	✓	✓	✓
AC circuit breaker		—	✓	✓	✓	✓	✓	✓
Engine switch		✓	✓	✓	✓	✓	✓	✓
Wheel		—	—	—	✓	✓	✓	✓
PACKAGE DIMENSIONS	Dimension (L x W x H) (mm)	447 x 353 x 475	560 x 445 x 450			700 x 525 x 580	950 x 560 x 730	
	Net Weight (kg)	31	40	48	51	74	110	120

* SE type is a Silent Electric type.

* Specifications are subject to change without prior notice.



PT RUTAN
Pusat Belanja Mesin Pertanian

